

NEWTON 3 HL 10 102 00

HS Code : 85131000
Barcode : 3700671407791



400
Lumens



100g
Weight



80m
Range



IP65
Rating



Li-Po
Battery
(3,8V /
1100 mAh)
(supplied)



2m
Shock
Resistant



USB Type-C
Charger
(supplied)

	Brightness	Running Time
Focused 100%	400 lumens	2 hours 20 mins*
Focused 50%	200 lumens	4 hours 30 mins*
Focused 5%	20 lumens	18 hours*
Flood 100%	400 lumens	2 hours 20 mins*

Charging time: 3h30

Charging indicator: Red - charging
Green - full

*with Li-Po battery

Dimensions

69 x 46 x 39 mm / Printed box: 171 x 109 x 50 mm

Safety

Directive **2014/30/UE**
2001/95/UE
2011/65/UE
2012/19/UE



LED Risk(c): Group 0 (no risk) - No photobiological hazard. Measures under NF EN 62471 Standard.

Assets

- **Hybrid Battery type: 3AAA Alkaline or Li-Po battery**
- Wide light beam (up to 90°).
- IP65: Excellent water and dust resistance.
- Easy to use: Only two buttons.

Use

Flood for working near feet area; **Focused** for work within easy reach.

Indication of remaining capacity in the battery
<10% the light will blink 3 times.

Temperatures: -10°C / +40°C.

Application: Industry, Construction, Maintenance, Roadworks, Networks & Work at height (also suitable for leisure, climbing and outdoor activities).